

HAUTONGA

Integrated Amplifier



A perfectly equipped and well balanced piece, the Hautonga further builds on the ground-breaking development of preceding Plinius integrated amplifiers.

Careful attention has been paid to signals and circuit layout with shorter signal paths, optimal component placement and a new wiring specification working in harmony to extract exciting new depth and detail from any musical recording.

The rear panel is outfitted with five line level RCA inputs with Phono RCA and a balanced XLR

pair additional as standard. Pre Out remains as does the Line Out connection for archiving or other ancillary equipment. The addition of trigger in and out connectors provide for multi-room or home theatre simplicity.

Scroll through inputs or access HT Bypass using the full function remote. Mute and volume controls are standard, as is the

display brightness adjustment and the full complement of CD player functions. A standby mode for true low power operation conserves energy while keeping the circuit active to deliver peak performance with minimal delay.

Taking integrated refinement to a new level, the Hautonga is an amplifier determined to realise the peak of its potential.

PLINIUS

The heart of music
www.pliniusaudio.com

HAUTONGA

Integrated Amplifier



POWER

200 watts RMS per channel into 8 ohms
280 watts RMS per channel into 4 ohms
Both channels driven from 20Hz to 20kHz at less than 0.2% total harmonic distortion

FREQUENCY RESPONSE

20Hz to 20kHz +/-0.2dB
-3dB at 5Hz and -3dB at 70kHz

DISTORTION

Typically <0.05% THD at rated power
0.2% THD and IM worst case prior to clipping

CURRENT OUTPUT

40A short duration peak per channel
Fuse protected

SLEW RATE

50V/ μ s

HUM & NOISE

90dB below rated output 20Hz to 20kHz
unweighted

GAIN

Line inputs to speaker out: 40dB
Phono Input To Pre Out: 66dB on high gain, 60dB on low gain

INPUT IMPEDANCE

47k ohms all inputs

RATED PRE OUT LEVEL

1.5V RMS into 47k ohms or higher

PRE OUT SOURCE IMPEDANCE

Typically 1.5k ohms

PRE OUT MINIMUM RECOMMENDED LOAD

47k ohms

LINE OUT LEVEL

190mV at 200 ohms

POWER/CURRENT CONSUMPTION

600VA
0.4A (92W) Class AB Idle
0.14A (32W) Standby

PRODUCT FEATURES

5 x RCA Line Inputs
1 x XLR/RCA selectable Line Input
1 x RCA HT Bypass Input
1 x RCA Output
1 x XLR Output
1 x Line Out
Trigger In/Out
Remote RC5 In
Ground Lift Switch
Optional Phono Input
Full function remote control
Available in black or silver

DIMENSIONS

Height: 120mm (4.75")
Width: 450mm (17.75")
Depth: 400mm (15.75")
Weight: 14kg (30lbs)



PLINIUS

The heart of music
www.pliniusaudio.com