

HIATO

Integrated Amplifier



Exceeding the power output of previous Plinius integrated amplifiers, the Hiato uses amplifier design concepts from some of our most prestigious units.

The Hiato combines the power supply, preamp stage and amplifier stage in a manner that allows you to enjoy all types of musical entertainment and sacrifice very little from the effect of using separate components for these functions.

A comprehensive rear panel layout includes four line level inputs and a user adjustable phono input. High quality WBT RCA connectors are used on all line level and phono inputs with

additional balanced XLR inputs for CD and Line 1. For home theatre system integration, the Hiato features the HT bypass input, remote IR input and 12V input/output triggers. A small unobtrusive 3.5mm jack on the front panel allows a casual user to connect portable media without needing to access the rear panel.

The output connections of the Hiato consist of four pairs of output connectors allowing bi-wired speaker applications, line

level output for archiving and pre-out for bi-amping.

The simple user interface allows for simple, delightfully clear and intuitive operation. The full function remote control also controls Plinius CD players.

The aluminium wrap and stylish wrap over lid fit with other products in the Plinius range while lifting handles allow you to manoeuvre the unit into place on a rack quite easily.

PLINIUS

The heart of music
www.pliniusaudio.com

HIATO

Integrated Amplifier



POWER

300 watts RMS per channel into 8 ohms
450 watts RMS per channel into 4 ohms
Both channels driven from 20Hz to 20kHz at less than 0.2% total harmonic distortion

FREQUENCY RESPONSE

20Hz to 20kHz +/-0.2dB
-3dB at 70kHz

DISTORTION

Typically <0.05% THD at rated power
0.1% THD and IM worst case prior to clipping

CURRENT OUTPUT

50A short duration peak per channel
Fuse protected

SLEW RATE

50V/ μ s

HUM & NOISE

90dB below rated output 20Hz to 20kHz unweighted

PHONO INPUT

RCA Unbalanced Input

ADJUSTABLE GAIN

50dB, 56dB, 60dB, 66dB

ADJUSTABLE LOAD

47k, 470R, 100R, 47R, 22R

FREQUENCY RESPONSE

20Hz to 20kHz +/-0.2dB
within RIAA spec

SIGNAL TO NOISE RATIO

-80dB wrt 5mV input, A weighted

DISTORTION

<0.01% THD at all levels below clipping

POWER/CURRENT CONSUMPTION

1100VA
0.6A (138W) Class AB Idle
0.3A (69W) Standby

PRODUCT FEATURES

5 x RCA Line Inputs
1 x XLR/RCA selectable Line Input
1 x RCA HT Bypass Input
1 x RCA Output
1 x XLR Output
1 x Line out
Trigger In/Out
Remote RC5 In
Ground Lift Switch
Optional Phono Input
Full function remote control
Available in black or silver

DIMENSIONS

Height: 170mm (7.5")
Width: 450mm (17.75")
Depth: 455mm (17.75")
Weight: 25kg (56lbs)



PLINIUS

The heart of music
www.pliniusaudio.com